

## Plus PL110E

TYPE	Pass-through dishwasher
LINE	PLUS LINE
BASKET	500x500
SIZE	620x770x1470/1930h




The PLUS line models are equipped with an automatic water softener that offers the possibility to break-down the formation of limestone with extreme efficiency. In fact, the water softener is completely autonomous and automatically controls its regeneration intervals according to the hardness of the inlet water; all you have to do is fill the salt tank whenever the message "lack of salt" appears on the display. The resins are regenerated during wash cycles, so no machine downtime is required.


The PL110E hood type dishwasher is the right solution for businesses that are faced with the washing of different types of dishes, proving capable of washing glasses, dishes, medium sized objects and GN 1/1 baking trays in only 620 mm wide, ensuring a maximum productivity of 60 baskets/hour (1080 dishes/hour). The hood type models are fitted with an easily removable basket support for easy cleaning and a rounded moulded tank with integral filters for perfect draining and absolute hygiene. The "PUSH TO START" cycle start system ensures less waste, preventing the start of empty washes.

The electronic control allows you to manage various parameters to give you an absolute customisation level and the continuous self-diagnosis allows you to minimise machine downtime, suggesting some operations to be verified. The self-cleaning cycle at the end of the day cleans the wash tank and empties the boiler from the hot water, preventing limestone forming inside. The standard double peristaltic electric rinse-aid and detergent dispenser ensures the best result from each wash cycle with great savings thanks to the precise dosage managed by the electronic card; whereas, the moulded washing and rinsing arms ensure great reliability and durability. The Thermo-stop function checks that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of AISI 304 steel and has been designed with all components in the front to allow easy technical assistance. Sturdy and reliable dishwashers to best deal with every moment of your day.









## DISHWASHERS FEATURES PLUS LINE PL110E

DISHWASHERS FEATURES PLUS LINE PL110E	
Dimensions - (mm) L - P - H	620x770x1470/1930h
n° baskets/hour - (+55°C)	Max 60
Height glass max	390mm
Ø height plate max	415mm
Height pot max	390mm
T bread basket	40 (H=390mm)
Trays	GN1/1
Fank heating element - Tank capacity	4,5kW - 37l
Boiler heating element - Boiler capacity	5,4kW - 7,3l
Vashing pump	1,34kW / 1,8Hp
Fotal power input / Current	6,74kW / 16A
Standard input voltage	400V3N - 50Hz
Recommended inlet water temperature	+55°C
Nater hardness	>15°f - 40°f
Vater consumption per cycle (inlet suggested pressure 2 BAR)	2,4 l
Adjustable detergent and rinse-aid dispenser	STANDARD
Built-in water softener	STANDARD
STANDARD EQUIPMENT	
Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	2
3 division cutlery insert	1
ntegral tank filter	STANDARD
Salt funnel	1
OPTIONAL	
Dptional 230V/3+T	•
Booster pump kit 0,5Hp	•
Drain pump kit 32W with Ecoclean	•
Boiler heating element 9kW	•
Basket for trays with 4 compartments dim.500x500x200mm	•
nclined basket for wine glasses dim.500x500x170mm	•
Remote control with LCD display	•
	■ OPTIONAL INSTALLABILE, ■ = OPTIONAL NON INSTALLABIL

