




Tunnel TM1210

TYPE	Rack conveyor dishwashers
LINE	TUNNEL LINE
BASKET	500x500
SIZE	1750x770x1825h mm



The TUNNEL Line has been designed to meet the needs of every customer, thanks to the various accessories installable, combining large workloads and optimising spaces available, simplifying operator work and reducing consumption. The models of this line are equipped with a double filtration system that retains all residues, whereas the vertical wash pumps and stainless steel wash arms ensure great performance. TUNNEL is also equipped with counterbalanced doors with double wall and anti-fall system and rounded moulded tanks.



400V3N+T 24,20kW
(CABLE NOT PROVIDED)

G 3/4" M
55°C
L=1500

A:Ø1"1/2 M
A1: Ø31 M
L=1500

STANDARD EQUIPMENT

Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	2

DISHWASHERS FEATURES TUNNEL LINE TM1210

Dimensions - (mm) L - P - H	1750x770x1825h mm
Basket dimensions	500x500 mm
n° baskets/hour	120/60
Passage height max (cm)	450 mm
Total power input	28,5 kW (50°C) - 35 kW (15°C)
Standard input voltage	400V3N - 50 Hz

WASHING

Tank capacity (lt)	70 lt
Washing pump	1,5 kW - 2 hp
Tank heating element (kW)	10,5 kW

FINAL RINSING

Boiler heating element (kW)	9,5 kW
Water consumption	150 lt/h
Inlet water temperature (°C)	+50°C
Minimum water pressure (BAR)	2 bar
Water hardness (°f)	7°f - 10°f

DRYING

Fan	0,55 kW
portata_d_aria_asciugatura	1400 m3/h
Heating element	6 kW

STANDARD EQUIPMENT

Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	2
4 division cutlery insert	1
Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	2

OPTIONAL

Pressure reducer with pressure gauge	●
Break-Tank and 200W rinse pump	●
Option extra power 9,5 Kw	●
Steam condensate module	●



Steam extractor with fan	●
Steam outlet chimney	●
Internal detergent & rinse-aid dosing unit	●
Triple tank filter and stainless steel drawer	●

● = OPTIONAL INSTALLABILE, ■ = OPTIONAL NON INSTALLABILE

