



Tunnel TM4110

TYPE	Rack conveyor dishwashers
LINE	TUNNEL LINE
BASKET	500x500
SIZE	2519x770x1810h mm



The TUNNEL Line has been designed to meet the needs of every customer, thanks to the various accessories installable, combining large workloads and optimising spaces available, simplifying operator work and reducing consumption. The models of this line are equipped with a double filtration system that retains all residues, whereas the vertical wash pumps and stainless steel wash arms ensure great performance. TUNNEL is also equipped with counterbalanced doors with double wall and anti-fall system and rounded moulded tanks.



400V3N+T 26,30kW
(CABLE NOT PROVIDED)



G 3/4" M
B: 55°C
B1: 10°C
L=1500



Ø1"1/2 M
L=1500

STANDARD EQUIPMENT

Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	2

DISHWASHERS FEATURES TUNNEL LINE TM4110

Dimensions - (mm) L - P - H	2519x770x1810h mm
Basket dimensions	500x500 mm
n° baskets/hour	270/200/140
Passage height max (cm)	450 mm
Total power input	28,6 kW (15°C)
Standard input voltage	400V3N - 50 Hz

PRE-WASHING

Tank capacity (lt)	70 l
Washing pump	1,5 kW - 2 Hp

WASHING

Tank capacity (lt)	70 l
Washing pump	1,5 kW - 2 Hp
Tank heating element (kW)	10,5 kW

FINAL RINSING

Break-Tank and rinse pump	0,2 kW
Boiler heating element (kW)	14 kW
Water consumption	~ 220 l/h
Inlet water temperature (°C)	+15°C
Minimum water pressure (BAR)	2 bar
Water hardness (°f)	7°f - 10°f

RECUPERATORE_TERMICO_CALORE

Exhauster	0,2 kW
Air capacity	~ 70 m3/h

STANDARD EQUIPMENT

Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	2
4 division cutlery insert	1
Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	2

OPTIONAL

Corner pre-washing system	●
Corner dryer unit	●



Option extra power 9,5 Kw	●
Internal detergent & rinse-aid dosing unit	●
Triple tank filter and stainless steel drawer	●
	● = OPTIONAL INSTALLABILE, ▣ = OPTIONAL NON INSTALLABILE