

## **Tunnel TM6310**

**TYPE** Pass-through

dishwasher

LINE TUNNEL LINE

**BASKET** 500X500

**SIZE** 620x766x1470/1930h











The **SMART** range dishwashers guarantee maximum performance thanks to the **Acquatech System** installed as standard, which, by means of an atmospheric boiler and a rinse pump, maintains constant temperature and pressure and optimal water consumption.

The **SM100E** pass-through dishwasher is the right solution for businesses faced with washing different types of dishes, proving capable of washing glasses, plates, medium-sized items up to 500x500x390(h)mm and GN 1/1 trays in just 620mm width, guaranteeing a maximum throughput of 60 baskets/hour (1080 dishes/hour).

The pass-through models are equipped with an easily **removable basket support** for easy cleaning and a **rounded moulded tank with integral filters** to ensure perfect drainage and absolute hygiene. The '**PUSH TO START**' cycle start system ensures less waste by preventing the start of empty washes.


The **DIGIT** panel is a real highlight with its **4 wash cycles and an automatic drain cycle** (with drain pump installed). On the control panel, you can easily view the tank and boiler temperature, messages from the **self-diagnosis system**, the **Scheduled Maintenance warning** and the **Smart Start button**, which changes colour to always show the dishwasher's status. The simple and extremely effective electronic board gives the possibility to set and control the rinse and drain times, the wash and rinse temperatures and the relevant Thermostops, which are essential to guarantee an excellent washing result.


The body is made entirely of AISI 304 steel and is designed with all components at the front for easy servicing by the technician. Robust and reliable dishwashers to cope with every moment of your day.











DISHWASHERS FEATURES TUNNEL LINE TM6310	
Dimensions - (mm) L - P - H	620x766x1470/1930h
n° baskets/hour - (+55°C)	Max 60
Height glass max	390mm
Ø height plate max	415mm
Height pot max	390mm
LT bread basket	40 (H=390mm)
Trays	GN1/1
Tank heating element - Tank capacity	2,6kW - 24l
Boiler heating element - Boiler capacity	5,4kW - 7,3l
Washing pump	0,5 kW / 1,2 Hp
Total power input / Current	6,52 kW / 16A
Standard input voltage	400V3N - 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7°f - 10°f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,4 I
Adjustable detergent and rinse-aid dispenser	STANDARD
Acquatech system rinse	STANDARD
STANDARD EQUIPMENT	
Basket for glasses dim.500x500x100mm	1
Basket for 18 dishes dim.500x500x100mm	1
8 division cutlery insert	1
Integral tank filter	STANDARD
OPTIONAL	
Optional 230V/3+T	•
Drain pump kit 32W with Ecoclean	•
Boiler heating element 9kW	•
Stainless steel tank filter	•
Reverse osmosis system	•
Inclined basket for wine glasses dim.500x500x170mm	•
Basket for trays with 4 compartments dim.500x500x200mm	•
Inclined basket for wine glasses dim.500x500x170mm	•
	•

lacktriangledown = optional non installabile, lacktriangledown = optional non installabile





